



05.0006/2017

DECLARATION OF PERFORMANCES

Annex III CPR - Regulation EU n. 305/2011 - Implementing Regulation EU n. 159/2014

Unique identification code of the product-type: **MONO.CHROME**

Intended use: One coat rendering mortar for external use (OC)

Manufacturer: Vimark S.r.l. - Strada Spartafino, 2 - 12016 Peveragno (CN) - Italia

Authorised representative: -

System/s of AVCP: System no. 4

Harmonised standard: EN 998-1:2010

Notified bodies: -

Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class A1	5.2.2 EN 998-1
Water absorption	W2	Table 2, L5 EN 998-1
Water permeability after weathering cycles	$\leq 1 \text{ ml/cm}^2$ after 48 h	Table 2, L7 EN 998-1
Water vapour permeability	$\mu \leq 10$	Table 2, L8 EN 998-1
Adhesion after weathering cycles	0.45 N/mm ² (FP) B	Table 2, L3 EN 998-1
Thermal conductivity	0.45 W/mK (tab. Mean value; P=50%)	Table 2, L10 EN 998-1
Durability	Evaluation based on provisions valid in the intended place of use of the mortar	5.2.3.2 EN 998-1
Dangerous substances	See MSDS	Note ZA.1 998-1

Appropriate Technical Documentation and/or Specific Technical Documentation: see technical data sheet
see MSDS

Website where the copy of the declaration of performance is made available: www.vimark.com/en/

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

06.03.2017

VIMARK S.r.l. Peveragno (CN) Italy

Marco Dutto



Vimark S.r.l.
Strada Spartafino, 2 - 12016 Peveragno (CN) Italy
14
05.0006/2017

EN 998-1:2010
MONO.CHROME

One coat rendering mortar for external use (OC)

Reaction to fire	Class A1
Water absorption	W2
Water permeability after weathering cycles	$\leq 1 \text{ ml/cm}^2$ after 48 h
Water vapour permeability	$\mu \leq 10$
Adhesion after weathering cycles	0.45 N/mm ² (FP) B
Thermal conductivity	0.45 W/mK (tab. Mean value; P=50%)
Durability	Evaluation based on provisions valid in the intended place of use of the mortar
Dangerous substances	See MSDS