



DILUENTE VIMAFLOOR S

Special thinner
for paint and primers



konstruktive • leidenschaft



Strada Spartafino, 2
12016 Peveragno (CN)



ph. +39 0171 38.38.00
Fax +39 0171 33.93.95



info@vimark.com
www.vimark.com



PRODUCT DESCRIPTION

DILUENTE PER VIMAFLOOR S is a specific thinner for alkyd-based paints and primers and some styrene-acrylic based paints. It can be used to remove and cleaning these paints and primers from tools. This diluting product is a specific for **VIMAFLOOR S**.

COMPOSITION

DILUENTE PER VIMAFLOOR S is a single-component liquid formula based on aliphatic and aromatic hydrocarbons.

MIXING AND APPLICATION

The product is ready for use. It is recommended to mix the formula in the drum before use. Add the correct amount of thinner to **VIMAFLOOR S**. mix the new formula in drum before applying.

INDICATIVE AMOUNTS REQUIRED

According to the amount of dilution need.

COLOUR

Clear.

PACKAGING

25 litres tin drums.

STORAGE

12 months in original intact packaging, protect from frost, not exposed to direct sunlight or heat sources.

RECOMMENDATIONS

Mix well before diluting **VIMAFLOOR S**.

PRODUCT DATA

Appearance	liquid	
Colour	clear	
Colour	max 15	APHA
Specific weight at + 15°C	0,80 ± 0,05 kg/l	EN ISO 2811
Distillation range P.I. °C	≥ 155 unit ≤ 188 unit	
Distillation range P.F. °C	≥ 155 unit ≤ 188 unit	
Acidity (MgKOH/g)	≤ 0,50 kg/m ²	
Copper corrosion	≤ 1A min	
Evaporation residue (g/100 ml)	≤ 0,005 %	
Humidity	≤ 500 ppm	

VOC

Product not intended for uses provided for by Directive 2004/42/CE.

REMARKS

Product for professional use. The data and instructions in this data sheet are based on our best practical and laboratory experience. They refer to laboratory tests and should be considered indicative. In view of the different conditions of use and application, which depend on factors over which Vimark has no control (type of surface, environmental conditions, technical indications for fixing, etc.), those who use the product are responsible for ascertaining whether or not it is suitable for the intended purpose. Thus our warranty obligation merely covers the quality and fade-free characteristics of the actual product, and exclusively in relation to the aforementioned data. Vimark reserves the right to make technical modifications without prior notice. This technical data sheet voids and substitutes all previous editions. Updates will be published on the web site www.vimark.com.

