



COMPRIMIBILE PERIMETRALE

Perimeter insulation strip
for flooring



konstruktive • **leidenschaft**



Strada Spartafino, 2
12016 Peveragno (CN)



ph. +39 0171 38.38.00
Fax +39 0171 33.93.95



info@vimark.com
www.vimark.com



PRODUCT DESCRIPTION

COMPRIMIBILE PERIMETRALE is a special closed cell, polyethylene foam insulating perimeter strip for concrete flooring, traditional screeds and self-levelling screeds for both domestic and industrial use.

The product is waterproof, rot-proof and is resistant to alkalis and chemical solutions.

COMPRIMIBILE PERIMETRALE strip is self-adhesive, which makes it fast and easy to install and is available in three different heights.

COMPOSITION

COMPRIMIBILE PERIMETRALE is made of closed cell polyethylene foam not containing CFC or HFCKW with acrylic based adhesive strips.

APPLICATION

Peel off the adhesive protection of **COMPRIMIBILE PERIMETRALE** and apply strips to wall along the entire perimeter before laying flooring. The excess strip must be trimmed and removed after all phases of the flooring are completed.

HEIGHT AVAILABLE

10.0 cm
15.0 cm
20.0 cm

COLOUR

Black.

PACKAGING

Rolls of 100 m.

PRODUCT DATA

Density	20.0-23.0 kg/m ³	
Compression property	0.124 kg/cm ²	ASTM D1621
Deformation at break	81.3 %	ASTM D638M
Exertion at break	2.3 kg/cm ²	ASTM D638M
Residual deformation	5.83 %	ASTM D1621
Water absorption	0.42 %	ASTM C272
Water vapour permeability	0,25 g/m ² after 24 hours	ASTM E96
Thermal conductivity	0.032 W/mK	EN 12667

REMARKS

Product for professional use. The data and instructions in this data sheet are based on our best practical and laboratory experience. They refer to laboratory tests and should be considered indicative. In view of the different conditions of use and application, which depend on factors over which Vimark has no control (type of surface, environmental conditions, technical indications for fixing, etc.), those who use the product are responsible for ascertaining whether or not it is suitable for the intended purpose. Thus our warranty obligation merely covers the quality and fade-free characteristics of the actual product, and exclusively in relation to the aforementioned data. Vimark reserves the right to make technical modifications without prior notice. This technical data sheet voids and substitutes all previous editions. Updates will be published on the web site www.vimark.com.

