



# GIUNTI PVC

Flexible concrete joint sealant  
for filling and sealing  
expansion joints  
in concrete flooring



konstruktive • **leidenschaft**



Strada Spartafino, 2  
12016 Peveragno (CN)



ph. +39 0171 38.38.00  
Fax +39 0171 33.93.95



info@vimark.com  
www.vimark.com




**PRODUCT DESCRIPTION**

GIUNTI PVC is a special flexible vinyl co-extruded resin, for filling and sealing saw cut joints in domestic or industrial concrete flooring whether internal or external. The special design and semi rigid structure prevents the sealant from shrinking in joints. The product can also fit inside small joints that can occur when cutting with partially worn discs. To install quickly we recommend using the specially designed installation equipment.

**COMPOSITION**

GIUNTI PVC is made of flexible vinyl co-extruded resin.

**WIDTH AVAILABLE (L)**



**AMOUNTS REQUIRED**

1.0 m product per 1.0 m joint to fill.

**COLOUR**

Black.

**PACKAGING**

Roll of 250 m.

**PRODUCT DATA WIDTH 3.5 mm**

Joint width	3,5 mm
Joint height	7,5 mm
Cutting disc thickness	2,4 mm
Type of cutting disc	diamond
Roll length	250 m

**PRODUCT DATA WIDTH 3.8 mm**

Joint width	3,8 mm
Joint height	7,7 mm
Cutting disc thickness	2,8 mm
Type of cutting disc	diamond
Roll length	250 m

**PRODUCT DATA WIDTH 5.2 mm**

Joint width	5,2 mm
Joint height	9,5 mm
Cutting disc thickness	3,2 mm
Type of cutting disc	diamond
Roll length	250 m

**REMARKS**

**Product for professional use.** The data and instructions in this data sheet are based on our best practical and laboratory experience. They refer to laboratory tests and should be considered indicative. In view of the different conditions of use and application, which depend on factors over which Vimark has no control (type of surface, environmental conditions, technical indications for fixing, etc.), those who use the product are responsible for ascertaining whether or not it is suitable for the intended purpose. Thus our warranty obligation merely covers the quality and fade-free characteristics of the actual product, and exclusively in relation to the aforementioned data. Vimark reserves the right to make technical modifications without prior notice. This technical data sheet voids and substitutes all previous editions. Updates will be published on the web site [www.vimark.com](http://www.vimark.com).

