



08.0018/2017

DECLARATION OF PERFORMANCES

Annex III CPR - Regulation EU n. 305/2011 - Implementing Regulation EU n. 159/2014

Unique identification code of the product-type: **MASTERFAST**

Intended uses: Improved cement adhesive with fast setting time and reduced slip for internal and external tiling C2-FT

Manufacturer: Vimark S.r.l. - Strada Spartafino, 2 - 12016 Peveragno (CN) - Italia

Authorised representative: -

System/s of AVCP: System no. 3
System no. 4 for reaction to fire

Harmonised standard: EN 12004:2012

Notified bodies: -

Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	F Class	EN 13501-1
Early tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$ after 6 hours	8.2 EN 1348:2007
Initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$	8.2 EN 1348:2007
Tensile adhesion strength after heat ageing	$\geq 1,0 \text{ N/mm}^2$	8.4 EN 1348:2007
Tensile adhesion strength after water immersion	$\geq 1,0 \text{ N/mm}^2$	8.3 EN 1348:2007
Tensile adhesion strength after freeze-thaw cycles	$\geq 1,0 \text{ N/mm}^2$	8.5 EN 1348:2007
Release of dangerous substances	See MSDS	4.5 EN 12004


Appropriate Technical Documentation and/or Specific Technical Documentation: see technical data sheet
see MSDS

Website where the copy of the declaration of performance is made available: www.vimark.com/en/

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

10.03.2017
VIMARK S.r.l. Peveragno (CN) Italy


Marco Dutto



Vimark S.r.l.
Strada Spartafino, 2 - 12016 Peveragno (CN) Italy
17
08.0018/2017

EN 12004:2012

MASTERFAST

Improved cement adhesive with fast setting time and reduced slip for internal and external tiling C2-FT

Reaction to fire	F Class
Early tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$ after 6 hours
Initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$
Tensile adhesion strength after heat ageing	$\geq 1,0 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 1,0 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 1,0 \text{ N/mm}^2$
Release of dangerous substances	See MSDS